



PINOUT CONFIGURATION

HD15 MALE		HD15 MALE	
1	RED CENTER	1	
2	GREEN CENTER	2	
3	BLUE CENTER	3	
6	RED SHIELD	6	
7	GREEN SHIELD	7	
8	BLUE SHIELD	8	
5		5	
4,10,11		4,10,11	
9		9	
12		12	
13		13	
14		14	
15		15	
SHELL — OVERALL BRAID — SHELL			

UNIT: mm

ITEM	DESCRIPTION	QTY.	UNIT
1	HD15 MALE CONNECTOR	2	PCS.
2	BLACK MOLDED PVC HOOD	2	PCS.
3	PAT.NO.: US 6,287,148 B1 RF-BLOK™SHIELDING METAL CAN	2	PCS.
4	BLACK 4/40 THUMBSCREW	4	PCS.
5	UL20276 (28AWG COAX+AL-FOIL+65% BRAID)x3C+26AWGx6C+AL-FOIL+DRAIN+BRAID OVERALL;BLACK PVC JACKET.	SEE	DWG.

VGA cable 10m black, both side Male Connector,
high resolution up to Full-HD, RF-BLOK

VGA Kabel 10m schwarz, beidseitig Male Connector,
hohe Auflösung bis zu Full-HD, RF-BLOK

P/N	L (mm)
CK-VGA02-100	10000±250
CK-VGA02-150	15000±250
CK-VGA02-200	20000±250
CK-VGA02-300	30000±250



WEEE-Reg.-Nr. DE 38986660

Date:
17.08.2022

SP

Checked by:
17.08.2022

FM

Datasheet:

CK-VGA02-XXX

