



UNIT: mm

ITEM	DESCRIPTION	QTY.	UNIT
1	HDMI TYPE A 19PIN CONNECTOR,MALE W/GOLD PLATED PINS UL94V-0	2	PCS.
2	PAT. US 6,287,148 B1 RF-BLOK™SHIELDING METAL CAN	2	PCS.
3	BLACK MOLDED PVC HOOD	2	PCS.
4	M3 THUMBSCREW WITH MOLDED P/N: TS-0204	2	PCS.
5	WHITE COLOR PAD PRINT	1	PCS.
6	HDMI CABLE; BLACK COLOR PVC JACKET LEVEL-2.51	SEE	DWG.

P/N	L ± (MM)
CK-HDMILK-005	5000 ± 50
CK-HDMILK-010	1000 ± 50
CK-HDMILK-020	2000 ± 50
CK-HDMILK-030	3000 ± 100
CK-HDMILK-050	5000 ± 150

NOTE:

1. THIS ITEM CONTAINS PAT. US 6,287,148 B1 RF-BLOK™SHIELDING DESIGN
2. PAD PRINT: 0.1M - 4.0M: HIGH SPEED HDMI® CABLE WITG ETHERNET SERIAL#:12AB1A
4.1M UP: STANDARD HDMI® CABLE WITH ETHERNET SERIAL#:12AB1A



HDMI cable Male - Male (length) black with LOK System, Resolution up to UHD/HDMI2.0, RF-BLOK shield

HDMI Kabel Stecker - Stecker (Länge) schwarz mit LOK System, Auflösung bis zu UHD/HDMI2.0, RF-BLOK Abschirmung



WEEE-Reg.-Nr. DE 38986660

Date:
10.08.2022

Checked by:
10.08.2022

Datasheet:

SP

FM



CK-HDMILK-XXX