



PINOUT CONFIGURATION

HD15 MALE	HD15 MALE
1 ——— RED CENTER	1
2 ——— GREEN CENTER	2
3 ——— BLUE CENTER	3
6 ——— RED SHIELD	6
7 ——— GREEN SHIELD	7
8 ——— BLUE SHIELD	8
5 ———	5
4,10,11	4,10,11
9 ———	9
12 ———	12
13 ———	13
14 ———	14
15 ———	15
SHELL ——— OVERALL BRAID ——— SHELL	

UNIT: mm

ITEM	DESCRIPTION	QTY.	UNIT
1	HD15 MALE CONNECTOR	2	PCS.
2	BLACK MOLDED PVC HOOD	2	PCS.
3	PAT.NO.: US 6,287,148 B1 RF-BLOK™SHIELDING METAL CAN	2	PCS.
4	BLACK 4/40 THUMBSCREW	4	PCS.
5	UL20276 (28AWG COAX+SPIRAL)x3C+28AWGx6C+AL-FOIL+ DRAIN+BRAID OVERALL;BLACK PVC JACKET.	SEE	DWG.

VGA cable (length) black, both side Male Connector, high resolution up to Full-HD, RF-BLOK  
 VGA Kabel (Länge) schwarz, beidseitig Male Connector, hohe Auflösung bis zu Full-HD, RF-BLOK

P/N	L (mm)
CK-VGA02-005	500 ± 50
CK-VGA02-010	1000 ± 50
CK-VGA02-020	2000 ± 100
CK-VGA02-030	3000 ± 100
CK-VGA02-050	5000 ± 150



WEEE-Reg.-Nr. DE 38986660

Date: 17.08.2022	SP
Checked by: 17.08.2022	FM
Datasheet:	CK-VGA02-XXX

