



**NOTE:**

1. CABLE: [(30AWG+1C+D+AL+ML)\*3C+(30AWGX4C)+(30AWGX2PAIRS)], AL-FOIL AND BRAID SHIELDED(AL)+ DRAIN WIRE (BARE COPPER), UL2919, BLACK PVC JACKET, SLOT  $\varnothing 7,5 \pm 0.15$ MM.(B-V0308-7D5-BK-01-B)
2. CONNECTOR: HIGH DENSITY D-SUB 15PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
3. METAL HEX NUT.
4. SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
5. MOLDED BLACK PVC.
6. TESTING: 100% ELECTRICAL TEST

VGA Pigtail Female - Female 0,2m black, one side cable entry about 100° for very small depth

VGA Pigtail Buchse - Buchse 0,2m schwarz, einseitiger Kabeleingang um 100° für sehr geringe Tiefe



WEEE-Reg.-Nr. DE 38986660

Date:  
18.08.2022

SP

Checked by:  
18.08.2022

FM

Datasheet:

CK-VGA05W-002

