



- NOTE:**
1. CABLE: [(32AWG x 3COAX, EACH COAX SPIRAL SHIELDED,) + (30AWG X 5C)+(30AWG x 2PAIRS)], OD: $\phi 5.3 \pm 0.15$ MM.
 2. CONNECTOR: P1&P2: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
 3. ALL SHELL SCREW, BLACK ZN PLATED.
 4. SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
 - 5 ALL HOOD: MOLDED BLACK (TNT-BK) PVC.
 6. 100% ELECTRICAL TESTING.

Mini VGA cable Male - Male (length) black, very small
 Connector molding and thin cable for good handling and small pack size
 Mini VGA Kabel Stecker - Stecker (Länge) schwarz, sehr klein
 Steckerumspritzung und dünnes Kabel für gute Handhabung und
 kleines Packmaß

Resolution up to WUXGA / 1920x1200

P/N	L(mm)	T(mm)
CK-VGA02-010MINI	1000	+50/-25
CK-VGA02-020MINI	2000	+50/-25
CK-VGA02-030MINI	3000	+100/-51



WEEE-Reg.-Nr. DE 38986660

Date:
17.08.2022

Checked by:
17.08.2022

Datasheet:

SP

FM

EVN
 electronic components GmbH
 MEDIA TECHNOLOGY

CK-VGA02-XXXMINI

Note: Technical modifications reserved; no responsibility is accepted for the accuracy of this information.