



NOTE:

- 1 CABLE: [#28(7/0.127 B.C.)x1P INS: Foam-PE+D.W(7/0.127 B.C.)+AL/MY+ Hot-melt-Mylar]x2C INS Polyolefin+AL/MY+B.D. PVC JACKET; OD 5.5±0.15mm.
2. CONNECTOR: P1: USB 3.0 A TYPE MALE
P2: USB 3.0 B TYPE MALE
3. HOOD: MOLDED TYPE, PVC 45P
4. ELECTRICAL TEST:
 - (1) 100% OPEN SHORT & MIS WIRE TEST.
 - (2) CONTACT RESISTANCE 3 ohm Max.
 - (3) INSULATION RESISTANCE 10Mohm Min.
5. PACKING EACH PC / POLY BAG

P1	PIN OUT	P2	
1	RED	1	PWR
2	WHITE	2	UTP_D-
3	GREEN	3	UTP_D+
4	BLACK	4	GND_PWRr†
5	BLUE	5	SDP1-
6	YELLOW	6	SDP1+
7	D.W	7	SDP1_Drain & SDP2_Drain
8	PURPLE	8	SDP2-
9	ORANGE	9	SDP2+
SHELL	B.D	SHELL	

USB3.0 cable Type A Male to Typ B Male, black

USB3.0 Kabel Typ A Stecker auf Typ B Stecker, schwarz

Partnumber	length (m)
CK-USB3.0AB-005SW24	0,5
CK-USB3.0AB-010SW24	1,0
CK-USB3.0AB-018SW24	1,8
CK-USB3.0AB-030SW24	3,0



WEEE-Reg.-Nr. DE 38986660

Date: 22.08.2022	SP
Checked by: 22.08.2022	FM
Datasheet:	

SP
FM

CK-USB3.0AB-XXXSW24