



NOTE:
1. JACKET PRINTING:

TTL[®] ULTRA FLEX HI-PQ[®] CABLE TOTAL TECHNOLOGIES LTD.[®]

UNIT: mm

ITEM	DESCRIPTION	QTY.	UNIT
1	HDMI TYPE A 19PIN MALE CONNECTOR GOLD PLATED PINS & SHELL UL94V-0; WITH TTL LOGO	2	PCS.
2	PAT. US 6,287,148 B1 RF-BLOK™ SHIELDING METAL CAN	2	PCS.
3	BLUE GRAY 5168C MOLDED PVC HOOD	2	PCS.
4	BLUE GRAY 5168C M3 THUMBSCREW WITH MOLDED P/N: TS-0204	1	PCS.
5	(100 Ω SHIELDED TWISTED PAIRS)x4C+(CONTROL WIRE)x7C+ AL-FOIL+DRAIN+SHIELD OVERALL; BLUE GRAY 5168C COLOR POLYOLEFIN ULTRA FLEX JACKET, WITH TTL JACKET PRINTING LEVEL-0.5	SEE	DWG.
6	#4/40 / M3 HEX-NUT	1	PCS.

UltraFlex High-Speed HDMI cable male - male blue/grey, RF-BLOK shield. Resolution up to UHD/HDMI 2.0. One connector with SupraLok System.

UltraFlex High-Speed HDMI Kabel Stecker - Stecker blau/grau, RF-BLOK Abschirmung. Auflösung bis zu UHD/HDMI 2.0. Ein Stecker mit SupraLok System.

CE



WEEE-Reg.-Nr. DE 38986660

Date:
11.08.2022

SP

Checked by:
11.08.2022

FM

Datasheet:

CK-HDMI-XXXUF1LK

