



Pin Assignment

Conn.1	Conn.2
1	12
2	11
3	10
4	9
5	8
6	7
7	6
8	5
9	4
10	3
11	2
12	1
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20

Electrical Test:

1. 100% Test(Open ,short ,miss wire)
2. Contact Resistance: 2 ohm max.
3. Insulation Resistance: 10M ohm min.
4. Hi-pot: 300V DC/10ms



7	WIRE:UL1007 28AWG BLACK	AR	PCS
6	NUT:#4-40UNC 10MM P4x10MM M4	2	PCS
5	Nickel plated nut:H4.75*2.0MM M4	2	PCS
4	Black PVC material 45P	AR	G
3	Transparent PE material	AR	G
2	DisplayPort F Pin Gold Plated Shell Nickel BLACK Insulation	2	PCS
1	Displayport F TO F Adapter PCBA	1	PCS
NO	DESCRIPTION	O'TY	UNIT

DisplayPort Gender Changer Female - Female with one side Screw Mount

DisplayPort Gender Changer Female - Female mit einseitiger Schraubmontage



WEEE-Reg.-Nr. DE 38986660

Date:
17.08.2022

SP

Checked by:
17.08.2022

FM

Datasheet:

CK-DPFF

